

DIV 6285

Izolacijska tipla D=10 sa duljom zonom eksp. i čavlom s glavom presvučenom plastikom

Hammer in fixing D=10 mm with long exp. zone and nail with plastic coated head



D	Dimenzija tiplje	Promjer okvira	Min dubina sidrenja	Iskoristiva duljina	
10	120	60	80-90	30-40	250
10	140	60	80-90	50-60	250
10	160	60	80-90	70-80	250
10	180	60	80-90	90-100	250
10	200	60	80-90	110-120	250
10	220	60	80-90	130-140	250
10	260	60	80-90	150-180	200
10	300	60	80-90	190-220	200

DIV 6286

Izolacijska tipla D=10 sa duljom zonom eksp. i vijkom sa šest. glavom presvučenom plastikom

Screw in fixing D=10 mm with long exp. zone and metal screw with plastic coated hex head



D	Dimenzija tiplje	Promjer okvira	Min dubina sidrenja	Iskoristiva duljina	
10	140	60	80-90	50-60	250
10	160	60	80-90	70-80	250
10	180	60	80-90	90-100	250
10	200	60	80-90	110-120	250
10	220	60	80-90	130-140	250
10	260	60	80-90	150-180	200
10	300	60	80-90	190-220	200

DIV 6287

Izolacijski okvir s maskirnom kapicom

Insulation flange with masking cap



Oznaka	Promjer okvira	Promjer vijka	
KC	60	5	200

DIV 6289

Okvir D=140 mm za pričvršćivanje izolacijskih ploča od fiberglasa male gustoće

Flange D=140 mm for fixing mineral-fibre insulation boards of low density



Oznaka	Promjer okvira	
KWL-140	140	200